

BEHR® OIL-BASED PRE STAIN WOOD CONDITIONER

- Prepares Wood Surfaces for Oil-Based Staining
- · Helps Prevent Streaks & Blotches
- Use Prior to Staining
- · Excellent Penetration
- · Helps Promote Even Staining











READY TO USE. PROTECT FROM FREEZING.

WHERE TO USE: Properly prepared Interior bare or stripped wood surfaces, prior to applying BEHR® Oil-Based Wood Stains. Not for use with water-based stains. For water-based stains, pretreat wood with BEHR Water-Based Pre-Stain Wood Conditioner.

SURFACE PREPARATION[†] (The following steps are recommended for best results.) Before applying BEHR Pre-Stain Wood Conditioner to bare or stripped wood surfaces, sand wood surfaces in the direction of the grain to desired smoothness. Remove all dust from the surface. Apply stain within two hours of application of BEHR Pre-Stain Wood Conditioner.

APPLICATION Stir thoroughly before using. Do not shake or thin. Use a nylon or nylon/polyester brush or a saturated clean cloth and apply liberally to all areas of the wood surface including edges. Allow to penetrate for 5 to 10 minutes, then remove any excess with clean, dry cloth. Apply BEHR Oil-Based Wood Stain or BEHR Oil-Based Stain & Poly In One. Follow all label instructions.

DRY TIME Dries in 10 minutes.

DISPOSAL For disposal of empty containers and unused product, contact your household refuse collection service.

LIMITED WARRANTY Visit behr.com/warranty or call 1-800-854-0133 Ext. 2 for more information.

*WARNING If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

▲ WARNING Cancer and Reproductive Harm www.P65Warnings.ca.gov

IMPORTANT! STORAGE AND DISPOSAL: DANGER! Rags, steel wool and waste soaked with BEHR OIL-BASED PRE-STAIN WOOD CONDITIONER may spontaneously catch fire if improperly discarded or stored. To avoid a spontaneous container, immediately after use, place rags, steel wool or waste in a sealed water-filled, metal container. Do not store unused product inside the home. For disposal guidance, contact your household refuse collection service, fire department, county or state government control agency.

DANGER! HARMFUL OR FATAL IF SWALLOWED. COMBUSTIBLE LIQUID AND VAPOR. CONTAINS: HYDROTREATED LIGHT DISTILLATES AND NAPHTHA (PETROLEUM). MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN, NOSE AND THROAT IRRITATION. NOTICE: Reports have associated repeated prolonged occupational exposure to solvents with permanent brain damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Keep away from heat and flame. Do not smoke. Prevent build-up vapors by opening all windows and doors to achieve cross-ventilation. Extinguish all flames and pilot lights and turn off stoves, heaters, electric motors, high intensity lights and other sources of ignition during use and until all vapors are gone. USE ONLY WITH ADEQUATE

VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH-approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, do not induce vomiting. Call physician immediately.

KEEP OUT OF REACH OF CHILDREN-DO NOT TAKE INTERNALLY.

